

Technology

- 1 STIHL 4-MIX® engine**
The STIHL 4-MIX® engine combines the advantages of both a two- and four-stroke engine. Lower consumption, fewer emissions, no need for oil servicing. Less obtrusive noise. Excellent engine power and high torque.

Comfort

- 2 Low-vibration handle design**
The frame grip ensures a significant reduction in vibrations. This reduces fatigue so you can keep on working for longer.
- 3 Multi-function handle**
All the engine control functions are integrated into the left handle. The machine can be controlled at the touch of a finger while you keep your hands in working position.
- 4 Large support cushion**
The large support cushion rests against your body or leg while you're drilling. This is not only very comfortable but it also helps you to control the auger more precisely and smoothly.

Safety

- 5 QuickStop drill brake**
The STIHL QuickStop drill brake with a release lever interrupts the power flow when the drill jams. The brake system makes it easy for jammed drills to be screwed back out.

i Please note that not all products are equipped with the features listed here. Only the most important features are described on this page. For further explanations and information, see page 240 onwards or online at www.stihl.com.au.



Earth augers and accessories

- Mobile and robust powerhouses for professionals
- For drilling holes in the ground, planting, building or taking soil samples
- Specially suitable for large areas that are hard to access
- Drills, shaft extensions, support cushions and drill chucks

BT 131^①



BT 130



Only while stocks last!

NEW

BT 131 will be released when BT 130 are depleted



36.3 cm³, 1.4 kW / 1.9 hp, 10.0 kg^②. One-man earth auger with QuickStop drill break. 4-MIX[®] engine with enlarged fuel tank, low-vibration handle frame, control handle with stop button, long-life air filter system, large support cushion.

Order No. 4313 011 2122

BT 360



60.3 cm³, 2.9 kW / 3.9 hp, 28.8 kg^②. Proven high torque engine for drilling work as a couple. With STIHL ElastoStart as standard, start lock and reverse rotation lock, long-life air filter system, additional stop switch for the second operator, fold-out frame.





Order No. 4308 206 0301

For suitable fuels and lubricants, see page 188 onwards.

^① Weight excluding fuel and drill bit

^② BT 131 will be introduced when BT 130 are depleted.

For retail pricing visit www.stihl.com.au

	Order number	Diameter (mm)	Length (mm)	Suitable for earth augers	Use	Plain	Tungsten
Accessories for earth augers							
Earth auger bit 	4404 680 2004	40 / 1 9/16"	695	BT 121, BT 130, BT 131	For all ground types.	-	-
	4404 680 2006	60 / 2 3/8"				4404 682 3101	7004 871 0113
	4404 680 2009	90 / 4"				4404 682 3102	7004 871 0114
	4404 680 2012	120 / 5"				4404 682 3103	7004 871 0115
	4404 680 2015	150 / 6"				4404 682 3104	7004 871 0116
	4404 680 2020	200 / 8"				4404 682 3105	7004 871 0117
Earth auger bit 	4400 000 4209	90 / 4"	700	BT 360	For all ground types.	4402 682 3100	-
	4400 000 4212	120 / 5"				4402 682 3105	-
	4400 000 4215	150 / 6"				4402 682 3110	-
	4400 000 4220	200 / 8"				4402 682 3120	-
	4400 000 4225	250 / 10"				4402 682 3130	-
	4400 000 4228	280 / 12"				4402 682 3135	-
	4400 000 4235	350 / 14"				4402 682 3140	-
PLANT SPIRAL earth auger bit 	4311 680 2515	150 / 6"	525	BT 121, BT 130, BT 131	Special drill bit for drilling bore holes for plants. Cylindrical shape.	Drill points for augers For BT 121 and BT 130 Threaded pilot bit for 90 mm - 200 mm Order No. 7004 871 9524 Tungsten carbide tipped Y pilot bit for 90 mm - 200 mm Order No. 7004 871 9413	
SOIL LOOSENER earth auger bit 	4404 680 1900	260 / 10"	660	BT 121, BT 130, BT 131	Special drill bit for loosening soil and planting.	Tungsten carbide tipped finger scribe (with nuts & bolts) Order No. 7004 871 9414 For BT 360 Plain tipped Order No. 4401 680 3300 Tungsten carbide tipped Order No. 7004 871 0105	

	Order number	Length (mm)	Suitable for earth augers	Use
Shaft extensions 	4311 680 2350	450	BT 121, BT 130, BT 131	For extending the earth auger bit in deep bore holes.
	4470 000 4205	500	BT 360	
	4470 000 4210	1,000		
Support cushion 	4313 748 2501	–	BT 121, BT 130, BT 131	As a replacement for the existing support cushion.
Drill chuck 	4311 680 4010	–	BT 121, BT 130, BT 131	For twist drills up to 13 mm diameter. For use with drills with cylindrical connectors.

	Order number	Displacement (cm ³)	Power output (kW/hp)	Weight (kg) ^①	Sound pressure level ^② (dB(A))	Sound power level ^② (dB(A))	Vibration level, left/right ^③ (m/s ²)	STIHL engine (2-MIX/4-MIX ^④)	Spindle speed (rpm)	Automatic decompression valve	STIHL ElastoStart	Long-life air filter system	QuickStop drill brake	Start lock/reverse rotation lock
BT 130 ^⑤ <small>*Only while stocks last!</small>	4313 011 2112	36.3	1.4 / 1.9	9.9	92	100	1.5/2.2	4-MIX [®]	200	●	–	●	●	●
BT 131 ^⑤ <small>NEW Available from Spring 2017!</small>	4313 011 2122	36.3	1.4 / 1.9	10.0	92	100	1.7/2.0	4-MIX [®]	200	●	–	●	●	●
BT 360	4308 200 0301	60.3	2.9 / 3.9	28.8	99	111	6.8/8.7	–	50	–	●	●	–	●

● As standard

① Weight excluding fuel and drill bit

② K factor according to Dir. 2006/42/EC = 2.5 dB(A)

③ K factor according to Dir. 2006/42/EC = 2 m/s²

④ Delivery without **drill** bit

⑤ With support cushion



9 Hand-held drills and accessories

- For joiners, workmen, municipal workers, gardeners and landscapers
- For drilling wood, erecting fences and benches and restoring timber structures
- For digging planting holes, for landscaping gardens with flowers to perennial plants
- Comprehensive range of practical accessories

BT 45 wood drill



27.2 cm³, 0.8 kW/1.1 hp, 4.8 kg^Q. Hand-held drill with powerful petrol engine for drilling wood. Quick-release chuck with a chuck width of 13 mm as standard. Two forward gears, reverse gear and neutral position.

Order No. 4314 200 0005

Water attachment set



To adapt the hand-held drill-to-drill core holes with water. Includes holder, hose connection with ball valve and coupling for core hole drill with 1/2" attachment up to 150 mm in diameter. For BT 45.

Order No. 4314 007 1005

Wood drill bits

Hardened and laterally ground with spiral and spurs. With six-socket connector.



320 mm long.

Diameter 13 mm

Order No. 4314 682 5001

460 mm long.

Diameter 19 mm

Order No. 4314 682 5002

Diameter 22 mm

Order No. 4314 682 5003

Diameter 25 mm

Order No. 4314 682 5004

Planting auger bits

Interchangeable head and M14 connection thread.



590 mm long.

Diameter 3" (76 mm)

Order No. 4314 680 1903

Diameter 4" (102 mm)

Order No. 4314 680 1904

Diameter 5" (127 mm)

Order No. 4314 680 1905

Water attachment adaptors

1/4" 
Order No. 4314 682 3904

5/8" 
Order No. 4314 682 3903

Drill chuck with key


 Chuck width 13 mm.
Order No. 4314 680 4001

Planting Auger handle



For drilling planting holes.
Order No. 4314 007 1001

For drilling wood without tools (not pictured).

Order No. 4314 007 1000

For drilling wood with key (not pictured).

Order No. 4314 007 1004

Strap



Ideal for supporting the machine hands-free.
 For BT 45.

Order No. 4314 710 6500

Harness



Enables easy transportation of the tool. For BT 45.

Order No. 4314 710 9000

Order number	Displacement (cm ³)	Power output (kW/hp)	Weight (kg) ^①	Sound pressure level ^② (dB(A))	Sound power level ^③ dB(A))	Vibration level, left/right ^④ (m/s ²)	Spindle speed lowest gear (rpm)	Spindle speed second gear (rpm)	Spindle speed reverse gear (rpm)	
BT 45	4314 200 0005	27.2	0.8 / 1.1	4.8	98	103	7.2/6.1	910	2,710	810

● Fitted as standard

② K factor according to Dir. 2006/42/EC = 2.5 dB(A)

③ K factor according to Dir. 2006/42/EC = 2 m/s²

④ Without **drill bit**

For suitable fuels and lubricants, see page 168 onwards.

① Weight excluding fuel, fully assembled